


# Material Safety Data Sheet

## Diesel Low Sulfur (LSD) and Ultra Low Sulfur Diesel (ULSD)



**HMIS III:**

HEALTH	<b>1</b>
FLAMMABILITY	<b>2</b>
PHYSICAL	<b>0</b>

0 = Insignificant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product name</b>	: Diesel Low Sulfur (LSD) and Ultra Low Sulfur Diesel (ULSD)		
<b>Synonyms</b>	: 888100004478		
<b>MSDS Number</b>	: 888100004478	<b>Version</b>	: 2.4
<b>Product Use Description</b>	: Fuel		
<b>Company</b>	: Tesoro Refining & Marketing Co. 300 Concord Plaza Drive, San Antonio, TX 78216-6999		
<b>Tesoro Call Center</b>	: (877) 783-7676	<b>Chemtrec (Emergency Contact)</b>	: (800) 424-9300

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

<b>Regulatory status</b>	: This material is considered hazardous by the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200).
<b>Signal Word</b>	: WARNING
<b>Hazard Summary</b>	: Toxic. Combustible Liquid

#### Potential Health Effects

<b>Eyes</b>	: Eye irritation may result from contact with liquid, mists, and/or vapors.
<b>Inhalation</b>	: Vapors or mists from this material can irritate the nose, throat, and lungs, and can cause signs and symptoms of central nervous system depression, depending on the concentration and duration of exposure.
<b>Skin</b>	: Skin irritation leading to dermatitis may occur upon prolonged or repeated contact. Liquid may be absorbed through the skin in toxic amounts if large areas of skin are repeatedly exposed. Long-term, repeated skin contact may cause skin cancer
<b>Ingestion</b>	: Harmful or fatal if swallowed. Do NOT induce vomiting. This material can irritate the mouth, throat, stomach, and cause nausea, vomiting, diarrhea and restlessness. Aspiration hazard if liquid is inhaled into lungs, particularly from vomiting after ingestion. Aspiration may result in chemical pneumonia, severe lung damage, respiratory failure and even death.

**Target Organs** : Central nervous system, Eyes, Skin, Kidney, Liver

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No.	Weight %
Fuels, diesel, No 2; Gasoil - unspecified	68476-34-6	60 - 100%
Nonane	111-84-2	1 - 5%
Naphthalene	91-20-3	1 - 5%
1,2,4-Trimethylbenzene	95-63-6	1 - 5%
Xylene	1330-20-7	1 - 5%
Sulfur	7704-34-9	15 ppm maximum

**SECTION 4. FIRST AID MEASURES**

<b>Inhalation</b>	: Move to fresh air. Give oxygen. If breathing is irregular or stopped, administer artificial respiration. Seek medical attention immediately.
<b>Skin contact</b>	: Take off all contaminated clothing immediately. Wash off immediately with soap and plenty of water. Wash contaminated clothing before re-use. If skin irritation persists, seek medical attention immediately.
<b>Eye contact</b>	: Remove contact lenses. Rinse thoroughly with plenty of water for at least 15 minutes. If symptoms persist, seek medical attention.
<b>Ingestion</b>	: Do not induce vomiting without medical advice. If a person vomits when lying on his back, place him in the recovery position. Seek medical attention immediately.
<b>Notes to physician</b>	: Symptoms: Dizziness, Discomfort, Headache, Nausea, Disorder, Vomiting, Lung edema, Aspiration may cause pulmonary edema and pneumonitis, Liver disorders, Kidney disorders.

**SECTION 5. FIRE-FIGHTING MEASURES**

<b>Form</b>	: Liquid
<b>Flash point</b>	: 38°C Minimum for #1 Diesel, 52°C Minimum for #2 Diesel
<b>Auto Ignition temperature</b>	: 257 °C (495 °F)
<b>Lower explosive limit</b>	: 0.6 %(V)
<b>Upper explosive limit</b>	: 4.7 %(V)
<b>Suitable extinguishing media</b>	: Carbon dioxide (CO2), Water spray, Dry chemical, Foam, Keep containers and surroundings cool with water spray.
<b>Specific hazards during fire fighting</b>	: Fire Hazard Do not use a solid water stream as it may scatter and spread fire. Cool closed containers exposed to fire with water spray.
<b>Special protective equipment</b>	: Wear self-contained breathing apparatus and protective suit. Use personal

**for fire-fighters** protective equipment.

**Further information** : Exposure to decomposition products may be a hazard to health. Isolate area around container involved in fire. Cool tanks, shells, and containers exposed to fire and excessive heat with water. For massive fires the use of unmanned hose holders or monitor nozzles may be advantageous to further minimize personnel exposure. Major fires may require withdrawal, allowing the tank to burn. Large storage tank fires typically require specially trained personnel and equipment to extinguish the fire, often including the need for properly applied fire fighting foam.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions** : Evacuate nonessential personnel and remove or secure all ignition sources. Consider wind direction; stay upwind and uphill, if possible. Evaluate the direction of product travel, diking, sewers, etc. to contain spill areas. Spills may infiltrate subsurface soil and groundwater; professional assistance may be necessary to determine the extent of subsurface impact. Ensure adequate ventilation. Use personal protective equipment.

**Environmental precautions** : Carefully contain and stop the source of the spill, if safe to do so. Protect bodies of water by diking, absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material. The use of fire fighting foam may be useful in certain situations to reduce vapors. The proper use of water spray may effectively disperse product vapors or the liquid itself, preventing contact with ignition sources or areas/equipment that require protection. Discharge into the environment must be avoided. If the product contaminates rivers and lakes or drains inform respective authorities.

**Methods for cleaning up** : Take up with sand or oil absorbing materials. Carefully shovel, scoop or sweep up into a waste container for reclamation or disposal - caution, flammable vapors may accumulate in closed containers. Response and clean-up crews must be properly trained and must utilize proper protective equipment (see Section 8).

**CERCLA Hazardous substances and corresponding RQs :**

Xylene	1330-20-7	100 lbs
Naphthalene	91-20-3	100 lbs
Nonane	111-84-2	100 lbs

**SECTION 7. HANDLING AND STORAGE**

**Handling** : Use only in area provided with appropriate exhaust ventilation. Handle and open container with care. Use only intrinsically safe electrical equipment approved for use in classified areas. Do not smoke near areas where material is handled or stored. Remove all sources of ignition. Emergency eye wash capability should be available in the vicinity of any potential splash exposure.

- Advice on protection against fire and explosion** : Keep away from sources of ignition - No smoking. Ground and bond containers during product transfers to reduce the possibility of static-initiated fire or explosion. Special slow load procedures for "switch loading" must be followed to avoid the static ignition hazard that can exist when higher flash point material (such as fuel oil) is loaded into tanks previously containing low flash point products - see API Publication 2003, "Protection Against Ignitions Arising Out Of Static, Lightning and Stray Currents."
- Dust explosion class** : Not applicable
- Advice on common storage** : Keep away from food, drink and animal feed. Incompatible with oxidizing agents. Incompatible with acids.
- Other data** : Emergency eye wash capability should be available in the near proximity to operations presenting a potential splash exposure.

**SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Exposure Guidelines**

List	Components	CAS-No.	Type:	Value
OSHA Z1	Xylene	1330-20-7	PEL	100 ppm 435 mg/m3
	Naphthalene	91-20-3	PEL	10 ppm 50 mg/m3
ACGIH	Diesel Fuel	68476-30-2	TWA	100 mg/m3
	Xylene	1330-20-7	TWA	100 ppm
		1330-20-7	STEL	150 ppm
	Naphthalene	91-20-3	TWA	10 ppm
		91-20-3	STEL	15 ppm
	Nonane	111-84-2	TWA	200 ppm

- Engineering measures** : Use adequate ventilation to keep gas and vapor concentrations of this product below occupational exposure and flammability limits, particularly in confined spaces. Use only intrinsically safe electrical equipment approved for use in classified areas.
- Eye protection** : Safety glasses or goggles are recommended where there is a possibility of splashing or spraying.
- Hand protection** : Gloves constructed of nitrile, neoprene, or PVC are recommended. Consult manufacturer specifications for further information.
- Skin and body protection** : If needed to prevent skin contact, chemical protective clothing such as of DuPont TyChem®, Saranex or equivalent recommended based on degree of exposure. The resistance of specific material may vary from product to product as well as with degree of exposure.
- Respiratory protection** : A NIOSH/ MSHA-approved air-purifying respirator with organic vapor cartridges or canister may be permissible under certain circumstances where airborne concentrations are or may be expected to exceed exposure limits or for odor or irritation. Protection provided by air-purifying respirators is limited. Refer to OSHA 29 CFR 1910.134, ANSI Z88.2-1992, NIOSH Respirator Decision Logic, and the manufacturer for additional guidance on respiratory protection selection. Use a

NIOSH/ MSHA-approved positive-pressure supplied-air respirator if there is a potential for uncontrolled release, exposure levels are not known, in oxygen-deficient atmospheres, or any other circumstance where an air-purifying respirator may not provide adequate protection.

**Hygiene measures** : Avoid repeated and/or prolonged skin exposure. Waterless hand cleaners are effective. Consider disposal of contaminated clothing rather than laundering to prevent the formation of flammable vapors which could ignite via washer or dryer. Emergency eye wash capability should be available in the vicinity of any potential splash exposure. Wash hands before eating, drinking, smoking, or using toilet facilities. Use good personal hygiene practices. DO NOT use gasoline, kerosene, solvents, or harsh abrasive skin cleaners to clean skin.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Form</b>	: Liquid
<b>Appearance</b>	: Clear, straw colored
<b>Odor</b>	: Characteristic petroleum (kerosene) odor
<b>Flash point - typical</b>	: 38 °C Minimum for #1 Diesel, 52 °C Minimum for #2 Diesel
<b>Auto Ignition temperature</b>	: 257 °C (495 °F)
<b>Thermal decomposition</b>	: No decomposition if stored and applied as directed.
<b>Lower explosive limit</b>	: 0.6 %(V)
<b>Upper explosive limit</b>	: 4.7 %(V)
<b>pH</b>	: Not applicable
<b>Freezing point</b>	: No data available
<b>Boiling point</b>	: 148 - 372 °C(298 - 702 °F)
<b>Vapor Pressure</b>	: < 2 mm Hg at 20 °C
<b>Density</b>	: 0.86 g/cm <sup>3</sup>
<b>Water solubility</b>	: Negligible
<b>Viscosity, dynamic</b>	: 1.7 - 40 mPa.s at 37.8 °C (100.0 °F)
<b>Percent Volatiles</b>	: 100 %

## SECTION 10. STABILITY AND REACTIVITY

<b>Conditions to avoid</b>	: Avoid high temperatures, open flames, sparks, welding, smoking and other ignition sources. Keep away from strong oxidizers. Viton ® ; Fluorel ®
<b>Materials to avoid</b>	: Strong oxidizing agents. Peroxides
<b>Hazardous decomposition products</b>	: Carbon monoxide, carbon dioxide and noncombusted hydrocarbons (smoke). Diesel exhaust particulates may be a lung hazard - see Section 11.
<b>Thermal decomposition</b>	: No decomposition if stored and applied as directed.
<b>Hazardous reactions</b>	: Keep away from oxidizing agents, and acidic or alkaline products.

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Carcinogenicity**

- NTP** : Naphthalene (CAS-No.: 91-20-3)
- IARC** : Naphthalene (CAS-No.: 91-20-3)
- OSHA** : No component of this product which is present at levels greater than or equal to 0.1 % is identified as a carcinogen or potential carcinogen by OSHA.
- CA Prop 65** : WARNING! This product contains a chemical known to the State of California to cause cancer.  
naphthalene (CAS-No.: 91-20-3)
- Skin irritation** : Irritating to skin.
- Eye irritation** : Irritating to eyes.
- Further information** : Studies have shown that similar products produce skin cancer or skin tumors in laboratory animals following repeated applications without washing or removal. The significance of this finding to human exposure has not been determined. Other studies with active skin carcinogens have shown that washing the animal's skin with soap and water between applications reduced tumor formation. Positive mutagenicity results have been reported. Repeated over-exposure may cause liver and kidney injury  
IARC classifies whole diesel fuel exhaust particulates as probably carcinogenic to humans (Group 2A). NIOSH regards whole diesel fuel exhaust particulates as a potential cause of occupational lung cancer based on animal studies and limited evidence in humans.

**Component:**

<b>Fuels, diesel, No 2; Gasoil - unspecified</b>	68476-34-6	<p><u>Acute oral toxicity:</u> LD50 rat Dose: 5,001 mg/kg</p> <p><u>Acute dermal toxicity:</u> LD50 rabbit Dose: 2,001 mg/kg</p> <p><u>Acute inhalation toxicity:</u> LC50 rat Dose: 7.64 mg/l Exposure time: 4 h</p> <p><u>Skin irritation:</u> Classification: Irritating to skin. Result: Severe skin irritation</p> <p><u>Eye irritation:</u> Classification: Irritating to eyes. Result: Mild eye irritation</p>
<b>Nonane</b>	111-84-2	<p><u>Acute oral toxicity:</u> LD50 mouse Dose: 218 mg/kg</p> <p><u>Acute inhalation toxicity:</u> LC50 rat Exposure time: 4 h</p>
<b>Naphthalene</b>	91-20-3	<p><u>Acute oral toxicity:</u> LD50 rat Dose: 2,001 mg/kg</p> <p><u>Acute dermal toxicity:</u> LD50 rat Dose: 2,501 mg/kg</p> <p><u>Acute inhalation toxicity:</u> LC50 rat Dose: 101 mg/l</p>

Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.  
Result: Mild skin irritation

Eye irritation: Classification: Irritating to eyes.  
Result: Mild eye irritation

Carcinogenicity: N11.00422130

**1,2,4-Trimethylbenzene** 95-63-6

Acute inhalation toxicity: LC50 rat  
Dose: 18 mg/l  
Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.  
Result: Skin irritation

Eye irritation: Classification: Irritating to eyes.  
Result: Eye irritation

**Xylene** 1330-20-7

Acute oral toxicity: LD50 rat  
Dose: 2,840 mg/kg

Acute dermal toxicity: LD50 rabbit  
Dose: ca. 4,500 mg/kg

Acute inhalation toxicity: LC50 rat  
Dose: 6,350 mg/l  
Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.  
Result: Mild skin irritation

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Eye irritation: Classification: Irritating to eyes.  
Result: Mild eye irritation

**SECTION 12. ECOLOGICAL INFORMATION**

**Additional ecological information** : Keep out of sewers, drainage areas, and waterways. Report spills and releases, as applicable, under Federal and State regulations.

**Component:**

**Naphthalene** 91-20-3

Toxicity to algae:  
EC50  
Species:  
Dose: 33 mg/l  
Exposure time: 24 h

**1,2,4-Trimethylbenzene** 95-63-6

Toxicity to fish:  
LC50  
Species: Pimephales promelas (fathead minnow)  
Dose: 7.72 mg/l  
Exposure time: 96 h

Acute and prolonged toxicity for aquatic invertebrates:  
EC50  
Species: Daphnia  
Dose: 3.6 mg/l  
Exposure time: 48 h

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal** : In accordance with local and national regulations.

## SECTION 14. TRANSPORT INFORMATION

### CFR

Proper shipping name : DIESEL FUEL  
UN-No. : UN1202 (NA 1993)  
Class : 3  
Packing group : III

### TDG

Proper shipping name : DIESEL FUEL  
UN-No. : UN1202 (NA 1993)  
Class : 3  
Packing group : III

### IATA Cargo Transport

UN UN-No. : UN1202 (NA 1993)  
Description of the goods : DIESEL FUEL  
Class : 3  
Packaging group : III  
ICAO-Labels : 3  
Packing instruction (cargo aircraft) : 310  
Packing instruction (cargo aircraft) : Y309

### IATA Passenger Transport

UN UN-No. : UN1202 (NA 1993)  
Description of the goods : DIESEL FUEL  
Class : 3  
Packaging group : III  
ICAO-Labels : 3  
Packing instruction (passenger aircraft) : 309  
Packing instruction (passenger aircraft) : Y309

### IMDG-Code

UN-No. : UN 1202 (NA 1993)  
Description of the goods : DIESEL FUEL  
Class : 3  
Packaging group : III  
IMDG-Labels : 3  
EmS Number : F-E S-E  
Marine pollutant : No

## SECTION 15. REGULATORY INFORMATION

OSHA Hazards : Combustible Liquid

Moderate skin irritant  
 Moderate eye irritant  
 Toxic by ingestion  
 POSSIBLE CANCER HAZARD

TSCA Status : On TSCA Inventory  
 DSL Status : All components of this product are on the Canadian DSL list.  
 SARA 311/312 Hazards : Fire Hazard  
 Acute Health Hazard  
 Chronic Health Hazard

SARA III US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

<u>Components</u>	<u>CAS-No.</u>
<b>Xylene</b>	1330-20-7
<b>1,2,4-Trimethylbenzene</b>	95-63-6
<b>Naphthalene</b>	91-20-3

PENN RTK US. Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

<u>Components</u>	<u>CAS-No.</u>
<b>Nonane</b>	111-84-2
<b>Naphthalene</b>	91-20-3
<b>1,2,4-Trimethylbenzene</b>	95-63-6
<b>xylene</b>	1330-20-7
<b>Fuels, diesel, No 2; Gasoil - unspecified</b>	68476-34-6

MASS RTK US. Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)

<u>Components</u>	<u>CAS-No.</u>
<b>Xylene</b>	1330-20-7
<b>1,2,4-Trimethylbenzene</b>	95-63-6
<b>Naphthalene</b>	91-20-3
<b>Nonane</b>	111-84-2

NJ RTK US. New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)

<u>Components</u>	<u>CAS-No.</u>
<b>Nonane</b>	111-84-2
<b>Naphthalene</b>	91-20-3
<b>1,2,4-Trimethylbenzene</b>	95-63-6
<b>Xylene</b>	1330-20-7
<b>Fuels, diesel, No 2; Gasoil - unspecified</b>	68476-34-6

California Prop. 65 : WARNING! This product contains a chemical known to the State of California to cause cancer.

Naphthalene

91-20-3

## SECTION 16. OTHER INFORMATION

### Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Prepared by** : GWU mbH  
Birlenbacher Str. 18  
D-57078 Siegen  
  
Germany  
  
Telephone: +49-(0)271-88072-0

**Revision Date** : 07/23/2008

---

65, 66, 105, 295, 1747