



Date 9/01/09

PHONE: 360-816-8540
800-888-5048
FAX: 360-816-8541
EMAIL: asphalt@albina.com
INTERNET: www.albina.com

801 Main Street, Vancouver, WA 98660

MATERIAL SAFETY DATA SHEET

Quick Identifier:

Manufacturer's Name: ALBINA ASPHALT

Address: 801 Main Street, Vancouver, WA 98660

Emergency Response 24 Hour Telephone Number: (800) 535-5053

Other information calls: (800) 888-5048

IDENTITY - SECTION I

Trade Name and Synonyms: MC-250

Case Number:

Chemical name: Liquid Asphalt

Chemical Family: Hydrocarbon

Formula: 453

HAZARDOUS INGREDIENTS - SECTION II

Principle Hazardous Components (Chemical and Common Names)	%	Threshold Limit Value (Units)
<i>Asphalt (Petroleum):</i>		5 mg/m ³ TWA
<i>Solvents:</i>	24	0.0
<i>Others:</i>	76	5 mg

PHYSICAL & CHEMICAL CHARACTERISTICS - SECTION III

<i>Boiling Point:</i>	437° F+
<i>Vapor Pressure (mm Hg @ 100° F):</i>	0.05
<i>Percent Volatile by volume:</i>	N/A
<i>Solubility in water:</i>	Insoluble
<i>Specific Gravity (H₂O=1.00):</i>	0.9659
<i>Vapor Density (Air @ 1):</i>	N/A
<i>Evaporation Rate(H₂O=1):</i>	N/A
<i>Appearance and Odor:</i>	Black viscous Semi-solid Petroleum odor

FIRE AND EXPLOSION HAZARD DATA - SECTION IV

<i>Flash Point:</i>	180°F, OTC
<i>Flammable limits in air % by volume:</i>	Lower N/A Upper N/A
<i>Extinguisher Media:</i>	Dry chemical type preferred
<i>Special Fire Fighting Procedures:</i>	Hot asphalt may ignite flammable mixture on contact.
<i>Unusual Fire Hazards:</i>	CO, CO ₂ and oxygenates can be formed upon combustion. Do not heat above flash point.

PHYSICAL HAZARDS - SECTION V

<i>Material:</i>	Stable
<i>Conditions to avoid:</i>	N/A
<i>Incomparability (materials to avoid):</i>	N/A
<i>Hazardous Decomposition products:</i>	N/A
<i>Hazardous Polymerization will:</i>	Not occur
<i>Conditions to avoid:</i>	N/A

HEALTH HAZARDS - SECTION VI

Effects of overexposure:

Pulmonary irritation possible. Prolonged or repeated contact may cause disorders, such as dermatitis, folliculitis, or oil acne. Vapors may cause dizziness or vomiting.

Emergency and First Aid procedures:

Eyes: Flush with water for at least 15 minutes, get medical attention.

Skin: Cool hot asphalt with cold water. If burned, do not remove asphalt, get medical attention. If not burned, remove with approved solvent.

SPECIAL PROTECTION INFORMATION - SECTION VII

<i>Respiratory protection:</i>	Approved particulate respirator to avoid exposure to hot fumes or mists
<i>Ventilation:</i>	N/A
<i>Protective gloves:</i>	And clothing if material is being handled hot
<i>Local Exhaust:</i>	As required to remove vapors of hot material
<i>Eye protection:</i>	Goggles if hot product is being sprayed or splashed
<i>Other protective clothing or equipment:</i>	N/A

SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES - SECTION VIII

Steps to be taken in case material is released or spilled:

Allow to cool, scoop up.

Waste disposal methods:

Controlled burning in compliance with local regulations or bury in approved land fill.

Precautions to be taken in handling and storing:

If handled hot avoid breathing fumes or mist. Avoid prolonged breathing of vapors. Other precautions: Launder contaminated clothing before using. Discard leather goods when contaminated, wash before eating or smoking.

Explanation of abbreviations: N/D - Not Determined
N/A - Not Applicable
TLV - Threshold Limit Value
TWA - Time Weighted Average

**DISCLAIMER OF LIABILITY
FOR ALBINA ASPHALT**

The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any representation or warranty, express or implied, regarding its accuracy or correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and maybe beyond our knowledge. For this and other reasons, we do not assume any responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.